

1AP7 Rec'd PCT/PTO 11 JUL 2006

PTO/SB/21 (09-04)

Approved for use through 07/31/2006. OMB 0651-0031

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

TRANSMITTAL FORM

(to be used for all correspondence after initial filing)

Total Number of Pages in This Submission

37

Application Number

10/580,618

Filing Date

24 May 2006

First Named Inventor

Hongyu Wang

Art Unit

Not Yet Assigned

Examiner Name

Not Yet Assigned

Attorney Docket Number

42390P21573

ENCLOSURES

(Check all that apply)

☐

Fee Transmittal Form

☐

Fee Attached

☐

Amendment/Reply

☐

After Final

☐

Affidavits/declaration(s)

☐

Extension of Time Request

☐

Express Abandonment Request

☐

Information Disclosure Statement

☒

Certified Copy of Priority Document(s)

☐

Reply to Missing Parts/
Incomplete Application

☐

Reply to Missing Parts
under 37 CFR 1.52 or 1.53

☐

Drawing(s)

☐

Licensing-related Papers

☐

Petition

☐

Petition to Convert to a
Provisional Application

☐

Power of Attorney, Revocation

☐

Change of Correspondence Address

☐

Terminal Disclaimer

☐

Request for Refund

☐

CD, Number of CD(s) _____

Landscape Table on CD

☐

After Allowance Communication to TC

☐

Appeal Communication to Board
of Appeals and Interferences

☐

Appeal Communication to TC
(Appeal Notice, Brief, Reply Brief)

☐

Proprietary Information

☐

Status Letter

☒

Other Enclosure(s) (please identify
below): Return Receipt Postcard

Remarks

Express Mail No. EV 841 072 627 US

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT

Firm Name

BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN, LLP
12400 Wilshire Boulevard, Seventh Floor, Los Angeles, California 90025-1030

Signature

Printed name

James C. Scheller

Date

7/11/2006

Reg. No.

31,195

CERTIFICATE OF MAILING

I hereby certify that this correspondence is being deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Mail Stop PCT, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date shown below:

Signature

Typed or printed name

Jessica Savage

Date

7/11/06

This collection of information is required by 37 CFR 1.5. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to 2 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: MS PCT, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

CERTIFIED COPY OF
PRIORITY DOCUMENT

中华人民共和国国家知识产权局
STATE INTELLECTUAL PROPERTY OFFICE
OF THE PEOPLE'S REPUBLIC OF CHINA



证 明
CERTIFICATE

本证明之附件是向中国专利局作为受理局提交的下列国际申请副本
THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY OF THE BELOW
IDENTIFIED INTERNATIONAL APPLICATION THAT WAS FILED WITH THE
CHINESE PATENT OFFICE AS RECEIVING OFFICE

申请号: PCT/CN2005/001754

INTERNATIONAL APPLICATION NUMBER

申请日: 24.10月 2005 (24.10.2005)

INTERNATIONAL FILING DATE

名称: METHOD OF REALIZING COMMANDS SYNCHRONIZATION IN
INVENTION SUPPORTING MULTI-THREADING NO-VOLATILE MEMORY
FILE SYSTEM

中华人民共和国国家知识产权局局长
COMMISSIONER OF THE STATE INTELLECTUAL PROPERTY
OFFICE OF THE PEOPLE'S REPUBLIC OF CHINA

二零零六年五月十七日

MAY 17 2006

HOME COPY

PCT

REQUEST

The undersigned requests that the present international application be processed according to the Patent Cooperation Treaty.

For receiving Office use only

PCT/CN2005 / 001754
International Application No.
4 · 10月 2005 (24 · 10 · 2005)
International Filing Date
PO/CN 中华人民共和国国家知识产权局 PCT International Application
Name of receiving Office and "PCT International Application"
Applicant's or agent's file reference (if desired) (12 characters maximum) FPEL05150053

Box No. I TITLE OF INVENTION
METHOD OF REALIZING COMMANDS SYNCHRONIZATION IN SUPPORTING
MULTI-THREADING NO-VOLATILE MEMORY FILE SYSTEM

Box No. II APPLICANT.

☐ This person is also inventor

Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country. The country of the address indicated in this Box is the applicant's State (that is, country) of residence if no State of residence is indicated below.)

INTEL CORPORATION
2200 Mission College Blvd.
Santa Clara, California 95052
United States of America

Telephone No.

Facsimile No.

Teleprinter No.

Applicant's registration No. with the Office

State (that is, country) of nationality:

US

State (that is, country) of residence:

US

This person is applicant
for the purposes of:☐ all designated
States☒ all designated States except
the United States of America☐ the United States
of America only☐ the States indicated in
the Supplemental Box

Box No. III FURTHER APPLICANT(S) AND/OR (FURTHER) INVENTOR(S)

Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country. The country of the address indicated in this Box is the applicant's State (that is, country) of residence if no State of residence is indicated below.)

WANG, Hongyu
Room 301, No. 8, Lane 158,
Baocheng Road, Minhang District
Shanghai 201100
P. R. of China

This person is:

☐ applicant only☒ applicant and inventor☐ inventor only (If this check-box is
marked, do not fill in below.)

Applicant's registration No. with the Office

State (that is, country) of nationality:

CN

State (that is, country) of residence:

CN

This person is applicant
for the purposes of:☐ all designated
States☐ all designated States except
the United States of America☒ the United States
of America only☐ the States indicated in
the Supplemental Box☒ Further applicants and/or (further) inventors are indicated on a continuation sheet.

Box No. IV AGENT OR COMMON REPRESENTATIVE; OR ADDRESS FOR CORRESPONDENCE

The person identified below is hereby/has been appointed to act on behalf
of the applicant(s) before the competent International Authorities as:

☒ agent☐ common
representative

Name and address: (Family name followed by given name; for a legal entity, full official designation. The address must include postal code and name of country.)

China Patent Agent (H.K.) Ltd.
22/F, Great Eagle Centre
23 Harbour Road, Wanchai
Hong Kong Special Administrative Region
The People's Republic of China

Telephone No.

(852)28284688

Facsimile No.

(852)28271018

Teleprinter No.

Agent's registration No. with the Office

☐ Address for correspondence: Mark this check-box where no agent or common representative is/has been appointed and the space above is used instead to indicate a special address to which correspondence should be sent.

Box No. V DESIGNATIONS

The filing of this request constitutes under Rule 4.9(a), the designation of all Contracting States bound by the PCT on the international filing date, for the grant of every kind of protection available and, where applicable, for the grant of both regional and national patents.

However,

- ☐ DE Germany is not designated for any kind of national protection
- ☐ KR Republic of Korea is not designated for any kind of national protection
- ☐ RU Russian Federation is not designated for any kind of national protection

(The check-boxes above may be used to exclude (irrevocably) the designations concerned in order to avoid the ceasing of the effect, under the national law, of an earlier national application from which priority is claimed. See the Notes to Box No. V as to the consequences of such national law provisions in these and certain other States.)

Box No. VI PRIORITY CLAIM

The priority of the following earlier application(s) is hereby claimed:

Filing date of earlier application (day/month/year)	Number of earlier application	Where earlier application is:		
		national application: country or Member of WTO	regional application:* regional Office	international application: receiving Office
item (1)				
item (2)				
item (3)				

☐ Further priority claims are indicated in the Supplemental Box.

The receiving Office is requested to prepare and transmit to the International Bureau a certified copy of the earlier application(s) (only if the earlier application was filed with the Office which for the purposes of this international application is the receiving Office) identified above as:

☐ all items ☐ item (1) ☐ item (2) ☐ item (3) ☐ other, see Supplemental Box

* Where the earlier application is an ARIPO application, indicate at least one country party to the Paris Convention for the Protection of Industrial Property or one Member of the World Trade Organization for which that earlier application was filed (Rule 4.10(b)(ii)): . . .

Box No. VII INTERNATIONAL SEARCHING AUTHORITY

Choice of International Searching Authority (ISA) (if two or more International Searching Authorities are competent to carry out the international search, indicate the Authority chosen; the two-letter code may be used):

ISA / CN

Request to use results of earlier search; reference to that search (if an earlier search has been carried out by or requested from the International Searching Authority):

Date (day/month/year)

Number

Country (or regional Office)

Box No. VIII DECLARATIONS

The following declarations are contained in Boxes Nos. VIII (i) to (v) (mark the applicable check-boxes below and indicate in the right column the number of each type of declaration):

Number of
declarations

- ☐ Box No. VIII (i) Declaration as to the identity of the inventor :
- ☐ Box No. VIII (ii) Declaration as to the applicant's entitlement, as at the international filing date, to apply for and be granted a patent :
- ☐ Box No. VIII (iii) Declaration as to the applicant's entitlement, as at the international filing date, to claim the priority of the earlier application :
- ☐ Box No. VIII (iv) Declaration of inventorship (only for the purposes of the designation of the United States of America) :
- ☐ Box No. VIII (v) Declaration as to non-prejudicial disclosures or exceptions to lack of novelty :

Box No. IX CHECK LIST; LANGUAGE OF FILING

This international application contains:	This international application is accompanied by the following item(s) (mark the applicable check-boxes below and indicate in right column the number of each item):	Number of items
(a) in paper form, the following number of sheets:	1. <input checked="" type="checkbox"/> fee calculation sheet	: 1
request (including declaration sheets) : 3	2. <input checked="" type="checkbox"/> original separate power of attorney	: 1
description (excluding sequence listing and/or tables related thereto) : 17	3. <input type="checkbox"/> original general power of attorney	:
claims : 6	4. <input type="checkbox"/> copy of general power of attorney; reference number, if any:	:
abstract : 1	5. <input type="checkbox"/> statement explaining lack of signature	:
drawings : 7	6. <input type="checkbox"/> priority document(s) identified in Box No. VI as item(s):	:
Sub-total number of sheets : 34	7. <input type="checkbox"/> translation of international application into (language):	:
sequence listing :	8. <input type="checkbox"/> separate indications concerning deposited microorganism or other biological material	:
tables related thereto :	9. <input type="checkbox"/> sequence listing in computer readable form (indicate type and number of carriers)	:
(for both, actual number of sheets if filed in paper form, whether or not also filed in computer readable form; see (c) below)	(i) <input type="checkbox"/> copy submitted for the purposes of international search under Rule 13ter only (and not as part of the international application) :	:
Total number of sheets : 34	(ii) <input type="checkbox"/> (only where check-box (b)(i) or (c)(i) is marked in left column) additional copies including, where applicable, the copy for the purposes of international search under Rule 13ter :	:
(b) <input type="checkbox"/> only in computer readable form (Section 801(a)(i))	(iii) <input type="checkbox"/> together with relevant statement as to the identity of the copy or copies with the sequence listing mentioned in left column :	:
(i) <input type="checkbox"/> sequence listing	10. <input type="checkbox"/> tables in computer readable form related to sequence listing (indicate type and number of carriers)	:
(ii) <input type="checkbox"/> tables related thereto	(i) <input type="checkbox"/> copy submitted for the purposes of international search under Section 802(b-quater) only (and not as part of the international application) :	:
(c) <input type="checkbox"/> also in computer readable form (Section 801(a)(ii))	(ii) <input type="checkbox"/> (only where check-box (b)(ii) or (c)(ii) is marked in left column) additional copies including, where applicable, the copy for the purposes of international search under Section 802(b-quater) :	:
(i) <input type="checkbox"/> sequence listing	(iii) <input type="checkbox"/> together with relevant statement as to the identity of the copy or copies with the tables mentioned in left column :	:
(ii) <input type="checkbox"/> tables related thereto	11. <input type="checkbox"/> other (specify):	:
Type and number of carriers (diskette, CD-ROM, CD-R or other) on which are contained the		
<input type="checkbox"/> sequence listing:		
<input type="checkbox"/> tables related thereto:		
(additional copies to be indicated under items 9(ii) and/or 10(ii), in right column)		
Figure of the drawings which should accompany the abstract:	Language of filing of the international application: EN	

Box No. X SIGNATURE OF APPLICANT, AGENT OR COMMON REPRESENTATIVE

Next to each signature, indicate the name of the person signing and the capacity in which the person signs (if such capacity is not obvious from reading the request).



For receiving Office use only		2. Drawings: <input type="checkbox"/> received: <input type="checkbox"/> not received:
1. Date of actual receipt of the purported international application: 24 · 10月 2005 (24 · 10 · 2005)		
3. Corrected date of actual receipt due to later but timely received papers or drawings completing the purported international application:		
4. Date of timely receipt of the required corrections under PCT Article 11(2):		
5. International Searching Authority (if two or more are competent): ISA /	6. <input type="checkbox"/> Transmittal of search copy delayed until search fee is paid	

For International Bureau use only
Date of receipt of the record copy by the International Bureau:

This sheet is not part of and does not count as a sheet of the international application.

PCT

FEE CALCULATION SHEET

Annex to the Request

For receiving Office use only

PCT/CN2005 / 001754
International Application No.

24 · OCT 2005 (24 · 10 · 2005)
Date stamp of the receiving Office

Applicant's or agent's
file reference

FPEL05150053

Applicant

INTEL CORPORATION etc.

CALCULATION OF PRESCRIBED FEES

1. TRANSMITTAL FEE

CNY500

T

CNY500-

2. SEARCH FEE

International search to be carried out by CN

CNY1500

S

CNY1500-

(If two or more International Searching Authorities are competent to carry out the international search, indicate the name of the Authority which is chosen to carry out the international search.)

3. INTERNATIONAL FILING FEE

Where items (b) and/or (c) of Box No. IX apply, enter Sub-total number of sheets } 34
Where items (b) and (c) of Box No. IX do not apply, enter Total number of sheets }

i1 first 30 sheets

CHF1400

i1

CHF1400-

i2

4

number of sheets
in excess of 30

x

CHF15
fee per sheet

=

CHF60

i2

CHF60-

i3

additional component (only if sequence listing and/or tables related thereto are filed in computer readable form under Section 801(a)(i), or both in that form and on paper, under Section 801(a)(ii)):

400 x

fee per sheet

i3

Add amounts entered at i1, i2 and i3 and enter total at I

CHF1 460

I

CHF1460-

(Applicants from certain States are entitled to a reduction of 75% of the international filing fee. Where the applicant is (or all applicants are) so entitled, the total to be entered at I is 25% of the international filing fee.)

4. FEE FOR PRIORITY DOCUMENT (if applicable)

P

5. TOTAL FEES PAYABLE

Add amounts entered at T, S, I and P, and enter total in the TOTAL box

CNY2000CHF1460

TOTAL

CNY2000-

CHF1460-

MODE OF PAYMENT



authorization to charge
deposit account (see below)



postal money order



cash



coupons



cheque



bank draft



revenue stamps



other (specify):

AUTHORIZATION TO CHARGE (OR CREDIT) DEPOSIT ACCOUNT

(This mode of payment may not be available at all receiving Offices)



Authorization to charge the total fees indicated above.



(This check-box may be marked only if the conditions for deposit accounts of the receiving Office so permit) Authorization to charge any deficiency or credit any overpayment in the total fees indicated above.



Authorization to charge the fee for priority document.


Receiving Office: RO

Deposit Account

Date:

Name:

Signature:



**METHOD OF REALIZING COMMANDS SYNCHRONIZATION
IN SUPPORTING MULTI-THREADING NON-VOLATILE MEMORY FILE
SYSTEM**

5 BACKGROUND

[0001] A file system of a non-volatile memory may be organized as a directory-file structure, such as a tree-shaped structure. A root of the tree may be a root directory. Going through the tree, the root directory may be associated with one or more directories and then the directories may be associated with one or more files. Each directory or file may have one or more sectors that may be dynamically allocated in the non-volatile memory at different locations. The sectors may be linked by a data structure, such as a sequence table. If there are multiple concurrent read/write commands on the same file or directory, a lower priority read/write may be pre-empted by a higher priority write. The higher priority write may move the sequence table to a new physical location (like replacement), after the higher priority write completes. However, the lower priority read/write command may not know the new location of the sequence table. A similar situation occurs for multiple writes on different files that may cause the parent directory location change.

20 BRIEF DESCRIPTION OF THE DRAWINGS

[0002] The invention described herein is illustrated by way of example and not by way of limitation in the accompanying figures. For simplicity and clarity of illustration, elements illustrated in the figures are not necessarily drawn to scale. For example, the dimensions of some elements may be exaggerated relative to other elements for clarity. Further, where considered appropriate,

3/10

reference labels have been repeated among the figures to indicate corresponding or analogous elements.

[0003] FIG. 1 illustrates an embodiment of a file system of a non-volatile memory.

5 [0004] FIG. 2 illustrates an embodiment of an information fragment in a file system of a non-volatile memory.

[0005] FIG. 3 illustrates an embodiment of a sequence table, in a file system of a non-volatile memory.

10 [0006] FIG. 4 illustrates an embodiment of a data structure, such as a track table and corresponding lists attached to the track table.

[0007] FIG. 5 illustrates an embodiment of a system of the present invention.

[0008] FIG. 6 is a flowchart illustrating an embodiment of a method that may be used to read a file or a directory of a non-volatile memory.

15 [0009] FIG. 7 is a flowchart illustrating an embodiment of a method that may be used to write a file or a directory of a non-volatile memory.

DETAILED DESCRIPTION

20 [0010] The following description describes techniques for realizing commands synchronization in supporting a non-volatile memory file system, for example multi-threading flash file system. In the following description, numerous specific details such as logic implementations, opcodes, means to specify operands, resource partitioning/sharing/duplication implementations, types and interrelationships of system components, and logic partitioning/integration choices are set forth in order to provide a more

thorough understanding of the present invention. However, the invention may be practiced without such specific details.

[0011] References in the specification to "one embodiment", "an embodiment", "an example embodiment", etc., indicate that the embodiment described may include a particular feature, structure, or characteristic, but every embodiment may not necessarily include the particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same embodiment. Further, when a particular feature, structure, or characteristic is described in connection with an embodiment, it is submitted that it is within the knowledge of one skilled in the art to effect such feature, structure, or characteristic in connection with other embodiments whether or not explicitly described.

[0012] Referring now to Fig. 1, a file system 100 of a non-volatile memory may comprise, for example, a tree-shaped directory-file structure. In one embodiment, file system 100 may comprise a root directory 110. Root directory 110 may comprise a root directory information fragment 112. In another embodiment, file system 100 may further comprise a directory 120; however, other embodiments may comprise a different number of directories. In another embodiment, file system 100 may comprise more levels of directories. Directory 120 may comprise a directory information fragment 122. In one embodiment, root directory information fragment 112 may comprise one or more entries that may each be associated with a directory information fragment. For example, entry 114 may comprise a pointer that may point to directory information fragment 122. In one embodiment, the pointer may point to a first sector of directory information fragment 122.



[0013] In one embodiment, file system 100 may further comprise a file 130; however, other embodiments may comprise a different number of files. For example, file 130 may comprise a file information fragment 140. Directory information fragment 122 may comprise an entry 124 that may be associated with file information fragment 140; however, other embodiments may comprise a different number of entries. For example, entry 124 may include a pointer that may point to the file information fragment 140, e.g., a first sector of file information fragment 140. In one embodiment, file 130 may further comprise zero or more sequence table, for example, a sequence table may be implemented using various data structures, such as lists, arrays, etc. In one embodiment, file 130 may comprise a root sequence table with zero or more child sequence tables, to accommodate different number of file data fragments. For example, FIG. 1 shows that file 130 comprise a root sequence table 150 with two child sequence tables 160a and 160b. In one embodiment, a sequence table may comprise one or more sectors.

[0014] Referring to FIG. 1, in one embodiment, file information fragment 140 may comprise an entry 141 that may be associated with root sequence table 150. For example, entry 141 may comprise a pointer that may indicate the location of root sequence table 150, e.g., a first sector of root sequence table 150. In another embodiment, file information fragment 140 may comprise one or more entries (for example, pointers) that may each point directly to a corresponding file data fragment, for example, file data fragments 171-176, if there is no need for a sequence table since the number of entries in file information fragment 140 is not less than that of the file data fragments in file 130.

POLICY 2000 0001 0001

[0015] In another embodiment, root sequenced table 150 may comprise one or more entries that may each be associated with a child sequence table. For example, root sequence table 150 may comprise entries 151 and 152 that may be associated with child sequence tables 160a and 160b, respectively.

5 In another embodiment, root sequence table 150 may comprise one or more entries that may each be associated with a corresponding file data fragment, if there is no need for a child sequence table since the number of entries in root sequence table 150 is not less than that of the file data fragments in file 130. In yet another embodiment, each of entries 151 and 152 may include a
10 pointer that may indicate the locations of child sequence tables 160a and 160b, respectively. For example, a pointer may point to a first sector of a child sequence table.

[0016] With reference to FIG. 1, file 130 may comprise one or more file data fragments, for example, file data fragments 171-176. In one embodiment,
15 child sequence tables 160a and 160b may comprise entries that may each be associated with file data fragments 171-176, respectively. For example, child sequence tables 160a and 160b may comprise pointers that may each indicate a location of a corresponding one of file data fragments 171-176. Although FIG. 1 shows that file 130 may comprise a root sequence table and
20 two child sequence table, in other embodiments, file system 100 may comprise a root sequence table and one or more child sequence table for a root directory or a directory to accommodate more directories and files, respectively. In another embodiment, file system 100 may comprise multi levels of child sequence tables.

15

[0017] Referring now to FIG. 2, an embodiment of an information fragment 200 is shown. For example, information fragment 200 may include root directory information fragment, directory information fragment or file information fragment. In one embodiment, information fragment 200 may comprise one or more sectors that may be continuous. In another embodiment, information fragment 200 may comprise a data structure of one or more entries 230 that may each indicate a location of a corresponding fragment that links to information fragment 200. For example, each of entries 212, 214 and 216 may comprise a pointer that may point to a fragment or a root sequence table (e.g., a first sector thereof) attached to information fragment 200; however, in other embodiments, information fragment 200 may comprise a different number of entries. For example, root directory information fragment 112 of FIG. 1 may comprise entry 114 (for example a pointer) that may be associated with directory information fragment 122. In another embodiment, information fragment 200 may comprise one or more blank entries reserved for future entries. For example, blank entries may follow existing entries. In yet another embodiment, information fragment 200 may comprise one or more entries that may have the same index or serial number. For example, entries 212, 218 and 222 may have the same serial number, such as "1". The last entry 222 of the three may be considered as a valid latest entry and entries 212 and 218 may be considered as invalid. Similarly, entries 214 and 220 may have the same serial number "2". The last entry 220 may be considered as a valid latest entry and entry 214 may be considered as invalid.

[0018] Referring to FIG. 3, an embodiment of a sequence table 300 is shown.

For example, sequence table 300 may include root sequence table or child



sequence table. In one embodiment, sequence table 300 may comprise one or more sectors that may be continuous. In another embodiment, sequence table 300 may comprise a data structure, such as lists, arrays, etc. For example, sequence table may comprise a first field 310 and a second field 320 to indicate linkage among fragments. For example, referring to FIG. 1, file data fragments 171-176 may link to file information fragment 140 via root sequence table 150 and child sequence tables 160a and 160b, wherein root sequence table 150 is a parent sequence table.

[0019] In one embodiment, the first field 310 may comprise a replacement

pointer field and the second field 320 may comprise a location pointer field. In another embodiment, the second field 320 may indicate a location of a fragment or a child sequence table that may attach to sequence table 300.

The first field 310 may represent a location of a new entry that updates an existing entry of the second field 320. For example, entry 321 of the second field 320 may comprise a location pointer 1 that is associated with an existing fragment. If the existing fragment is replaced by a new fragment or moved to a new location, entry 312 of the first field 310 may comprise a first replacement pointer that may point to entry 324, which may comprise a first new location pointer to the new fragment or new location to replace the first location pointer of entry 321. Moreover, entries 322 and 323 of the second field 320 may comprise a second and a third location pointers, respectively, that may each point to a fragment. Entry 314 of the first field 310 may comprise a third replacement pointer that may point to entry 325, which may comprise a third new location pointer to replace the third location pointer of entry 323.

[0020] Now referring to FIG. 4, an embodiment of a data structure 400 is shown. Data structure 400 may store information or primary information on one or more files and/or one or more directories being operated concurrently. Data structure 400 may be implemented in various forms, such as lists, arrays, etc. In one embodiment, the information may be used to identify the one or more files or directories. Referring to FIG. 4, a first element 416 may relate to a file and a second element 418 may relate to a directory. In one embodiment, data structure 400 may comprise a track table. In another embodiment, data structure 400 may comprise one or more fields, such as fields 411-415. For example, for each element, a first field 411 may comprise an identifier that may identify a file or directory that is operated by one of the concurrent operations; a second field 412 may indicate a location associated with the file or directory, for example, a location of a root sector or a first sector of the file or directory; a third field 413 may comprise an attribute that may indicate a type of the file or the directory; a fourth field 414 may indicate a number of elements in a list (for example, 420 or 430) associated with the file or the directory, such as a number of concurrent operations on the file or the directory; and a fifth field 415 may comprise a link to the list, such as an address or a pointer to a first element in the list. However, other embodiments may comprise different fields to accommodate different primary information. In another embodiment, data structure 400 may be dynamically allocated in a volatile memory. The number of elements in data structure 400 may depend on how many files or directories being operated, such as read or written, simultaneously.



[0021] FIG. 4 further shows an embodiment of a first list 420 and a second list 430 that may correspond to the first element 416 and the second element 418, respectively. In one embodiment, the first and second lists 420 or 430 may comprise various types of data structures, such as signal linked lists, double linked lists, arrays, vectors, etc. The first list 420 may comprise one or more elements to track progress of all concurrent operations on the same file that is indicated by element 416. In one embodiment, the first list 420 may comprise elements 421-423 that may be associated with operations, READ 1, READ 2 and WRITE 1, respectively; however, other embodiments may comprise a different number of elements to accommodate a different number of operations and may apply to different operations. In another embodiment, the first list 420 may be dynamically stored in a volatile memory and elements 421-423 may be dynamically allocated at different addresses of the volatile memory.

[0022] Referring to FIG. 4, in one embodiment, each element of the first list 420 may comprise a progress information or data field 424 that may comprise progress information or progress data about one of the concurrent operations, for example, locations or pointers of sectors being operated in the operation. For example, said sectors may belong to one or more information fragments or sequence tables. In another embodiment, said sectors may comprise a first sector of one or more information fragments or sequence tables. Each element of the first list 420 may further comprise link information or data field or a next element location field 426 that may link one or more elements, for example 421-423, relating to the same file or directory. For example, the next element location field 426 may comprise an address or a pointer to a next

element in the first list 420. For example, the next element pointer field 426 may indicate an address of a volatile memory where an element on a next operation is stored. For example, the first element 421 of the first list 420 may comprise locations of sectors being read in READ 1 and an address 1
5 associated with the next operation READ 2. In another embodiment, the last element 423 may comprise locations of sectors being written in WRITE 1 with a null next element location field, because there is not any next operation in the first list 420. Similarly, the second list 430 associated with a directory that is indicated by element 418 may comprise information of operations on the
10 directory. The description on the second list 430 may refer to that of list 420, and thus is omitted herein. Although the first and second lists 420 and 430 are illustrated as separated from data structure 400, in other embodiments, elements of each list may be included in data structure 400.

[0023] Now Referring to FIG. 5, a diagram of a system level overview

15 according to one embodiment of the present invention is illustrated. As shown in FIG. 5, the system 500 includes a processor 510, a non-volatile memory 520 and a volatile memory 530. Processor 510 may be any type of processor adapted to perform operations in non-volatile memory 520 or volatile memory 530. For example, processor 510 may be a microprocessor, a digital signal
20 processor, a microcontroller, or the like.

[0024] Non-volatile memory 520 may comprise non-volatile memory, or the like. Processor 510 and non-volatile memory 520 may be coupled by bus 515. Volatile memory 530 may comprise RAM, or the like. Processor 510 and volatile memory 530 may be coupled by bus 525. In one embodiment,
25 processor 510, non-volatile memory device 520 and the volatile memory 530



may be included on an integrated circuit board, and buses 515 and 525 may be implemented using traces on the circuit board. In another embodiment, processor 510, non-volatile memory 520 and the volatile memory 530 may be included within the same integrated circuit, and buses 515 and 525 may be implemented using interconnect within the integrated circuit.

[0025] Processor 510 may perform operations in non-volatile memory 520 or volatile memory 530. In one embodiment, processor 510 may perform operations in the method as shown in Figs. 6 and 7, which will be described in the following paragraphs. In one embodiment, processor 510 may be not dedicated to the use of non-volatile memory 520, and processor 510 may perform operations in non-volatile memory 520 or volatile memory 530 while also performing other system functions.

[0026] An example method is illustrated in FIG. 6 that may be used by processor 510 to read a file or a directory from non-volatile memory 520. In one embodiment, processor 510 may establish in volatile memory 530 a data structure, such as 400, that may comprise one or more elements, wherein each element may record primary information on a file or a directory being operated. In another embodiment, processor 510 may build up in the volatile memory one or more lists, such as 420 and 430, that may be attached to each element of the data structure 400 and may comprise progress information on all concurrent operations on the file or the directory identified by each element. In yet another embodiment, instead of using one or more lists, processor 510 may combine elements in lists 420 and 430 in data structure 400 for all concurrent operations. The following description on the method of FIG. 6 may make reference to the embodiment of FIG. 4; however, other embodiments

10/10

may adopt different data structures to track information on each concurrent operation.

[0027] In block 602, processor 510 may create a new element for a READ operation, for example, READ 1. Referring to the embodiment of FIG. 4, processor 510 may create in data structure 400 a new element 416 that may comprise information on a file, for example file A, being operated in READ 1, in response to determining that data structure 400 does not comprise an element regarding file A. In another embodiment, processor 510 may create in the first list 420 a new element 421 for READ 1 that may read one or more sectors of file A. Element 421 may be attached to element 416 of data structure 400. In yet another embodiment, processor 510 may combine elements 416 and 421 in the same data structure 400. In block 604, processor 510 may initialize the progress information in element 421. In one embodiment, processor 510 may store locations of sectors of file A being read in READ 1. In another embodiment, processor 510 may add the address of element 421 into a preceding element (not shown) of the first list 420.

[0028] In block 606, processor 510 may retrieve the progress information regarding a fragment, for example fragment X, of file A in element 421. In one embodiment, processor 510 may obtain one or more locations corresponding to one or more sectors belonging to fragment X. Processor 510 may read fragment X according to the locations as obtained in block 606 (block 608). In one embodiment, processor 510 may find the locations as obtained in block 606 and read fragment X therefrom. In block 610, processor 510 may update the progress information or data in element 421 in response to determining that the reading of fragment X is completed. In one embodiment, processor

510 may delete from element 421 the locations associated with fragment X.

In block 612, processor 510 may determine whether there is any other fragment being read in READ 1. In one embodiment, processor 510 may determine all the fragment(s) of file A have been read, in response to

5 determining that element 421 does not comprise a location of any sector being read, and processor 510 may remove element 421 for READ 1 from the first list 420 (block 614). In another embodiment, processor 510 may further update data structure 400 by removing element 416 if there is no more operation regarding file A. Conversely, processor 510 may continue to blocks 10 606, 608, 610 and 612, in response to determining that there are one or more fragments being read in READ 1. In one embodiment, processor 510 may determine whether there are one or more fragments being read in READ 1 based on the progress information or data of element 421. Although the method of FIG. 6 is described with particular reference to FIG. 4, other 15 embodiments may apply to a different operation on a different file or directory.

[0029] An example method is illustrated in FIG. 7 that may be used by processor 510 to write a file or a directory in non-volatile memory 520. In one embodiment, processor 510 may establish in volatile memory 530 a data structure, such as 400, that may comprise one or more elements, wherein 20 each element may record primary information on a file or a directory being operated. In another embodiment, processor 510 may build up in the volatile memory one or more lists, such as 420 and 430, that may be attached to each element of the data structure 400 and may comprise progress information on all concurrent operations on the file or the directory identified by each element.

25 In yet another embodiment, instead of using one or more lists, processor 510

may combine elements in lists 420 and 430 in data structure 400 for all concurrent operations. The following description on the method of FIG. 6 may make reference to the embodiment of FIG. 4; however, other embodiments may adopt different data structures to track information on each concurrent operation.

[0030] In block 702, processor 510 may create a new element for a WRITE operation, for example, WRITE 1. Referring to the embodiment of FIG. 4, processor 510 may create in data structure 400 a new element 416 that may comprise information on a file, for example file A, being operated in WRITE 1, in response to determining that data structure 400 does not comprise an element regarding file A. In another embodiment, processor 510 may create in the first list 420 a new element 423 for WRITE 1 that may write one or more sectors of file A. Element 423 may be attached to element 416 of data structure 400. In yet another embodiment, processor 510 may combine elements 416 and 423 in the same data structure 400. In block 704, processor 510 may initialize the progress information in element 423. In one embodiment, processor 510 may store locations of sectors of file A being written in WRITE 1. In another embodiment, processor 510 may add the address of element 423 into a preceding element (not shown) of the first list 420.

[0031] In block 706, processor 510 may retrieve the progress information regarding a fragment, for example fragment X, of file A in element 423. In one embodiment, processor 510 may obtain one or more locations corresponding to one or more sectors belonging to fragment X. Processor 510 may write fragment X according to the locations as obtained in block 706 (block 708). In



block 710, processor 510 may determine whether any sector or non-fragment unit or fragment replacement occurs during writing fragment X. For example, in response to determining that one or more sequence table associated with fragment X and/or fragment X are moved to one or more new physical locations (such as sector locations or non-fragment unit locations), processor 510 may update all elements of file A in the first list 420 relating to the location replacement with the one or more new locations (block 712). In one embodiment, processor 510 may replace one or more original sector locations in the first list 420 by corresponding new locations according the location moving. In block 714, processor 510 may update the progress information or data in element 423 in response to determining that the writing of fragment X is completed. In one embodiment, processor 510 may delete from element 423 the locations associated with fragment X.


[0032] In block 716, processor 510 may determine whether there is any other fragment being written in WRITE 1. In one embodiment, processor 510 may determine all the fragment(s) of file A have been written, in response to determining that element 423 does not comprise a location of any sector being written, and processor 510 may remove element 423 for WRITE 1 from the first list 420 (block 718). In another embodiment, processor 510 may further update data structure 400 by removing element 416 if there is no more operation regarding file A. Conversely, processor 510 may continue to blocks 706, 708, 710, 712, 714 and 716, in response to determining that there are one or more fragments being written in WRITE 1. In one embodiment, processor 510 may determine whether there are one or more fragments being written in WRITE 1 based on the progress information/data of element



423. Although the method of FIG. 7 is described with particular reference to FIG. 4, other embodiments may apply to a different operation on a different file or directory.

[0033] While the methods of FIGs. 6 and 7 are illustrated as a sequence of operations, processor 510 in some embodiments may perform illustrated operations of the method in a different order. In one embodiment, processor 510 may perform one or more concurrent operations simultaneously according to FIG. 6 and/or FIG. 7. In another embodiment, according to data structure 400, processor 510 may detect whether there is a high priority operation on a file or directory in all concurrent operations on the same file or directory before performing any of the concurrent operations. If processor 510 detects that there is such a high priority operation, processor 510 may perform the high priority operation according to FIGs. 6 or 7 first. Processor 510 may perform other concurrent operations after the completion of the high priority operation. In another embodiment, processor 510 may perform such detection during performing one of the concurrent operations. In response to detecting such a high priority operation, processor 510 may perform the high priority operation after completing the one concurrent operation on a fragment of the file or directory and processor 510 may continue the one concurrent operation on remaining fragment(s) of the file or directory upon the completion of the high priority operation.

[0034] In one embodiment, processor 510 may generate a new element in data structure 400 for each concurrent operation before performing any of the concurrent operations. For example, blocks 602 and 702 may be omitted from FIGs. 6 and 7, respectively. For example, a new element may comprise



information on a file or directory to be operated by a concurrent operation and progress information/data about the concurrent operation. In addition, data structure 400 may also comprise link information/data to link elements relating to the same file or directory. In another embodiment, processor 510
5 may add one or more elements that may each identify a file or directory being operated by the concurrent operations. In another embodiment, processor 510 may record progress information/data for each of the concurrent operations in a corresponding element of the data structure 400. In yet another embodiment, processor 510 may record progress information/data
10 for each operation as lists, etc. In one embodiment, processor 510 may perform initialize the progress information/data before executing any of the concurrent operations. For example, blocks 604 and 704 may be omitted from FIGs. 6 and 7, respectively.

[0035] While certain features of the invention have been described with
15 reference to embodiments, the description is not intended to be construed in a limiting sense. Various modifications of the embodiments, as well as other embodiments of the invention, which are apparent to persons skilled in the art to which the invention pertains are deemed to lie within the spirit and scope of the invention.



What is claimed is:

1. A method comprising
 creating a data structure to store progress information on one or more
 concurrent operations to access a file system of a non-volatile memory; and
 5 executing the one or more concurrent operations based on the progress info.

2. The method of claim 1 further comprising
 initializing the progress information to include one or more locations of a
 non-fragment unit of the file system being operated in each concurrent operations.

3. The method of claim 1 further comprising
 10 retrieving the progress information to obtain one or more locations of a non-
 fragment unit of the file system associated with each concurrent operation.

4. The method of claim 1 further comprising
 operating on a fragment of the file system as indicated by the progress
 information according to each concurrent operation.

15 5. The method of claim 1 further comprising
 updating the progress information associated with a concurrent operation, in
 response to the completion of the concurrent operation on a fragment of the file
 system.

6. The method of claim 5 further comprising
 20 from the progress information associated with the concurrent operation,
 deleting one or more locations of a non-fragment unit of the file system associated
 with the fragment.

7. The method of claim 1, further comprising

4D

continuing each concurrent operation on one or more fragments of the file system, in response to determining that the progress information associated with the concurrent operation comprises one or more locations of a non-fragment unit of the file system associated with the one or more fragments.

5 8. The method of claim 1 further comprising
removing the progress information for each concurrent operation, in response to determining that the concurrent operation on the file system is completed.

9. The method of claim 1 further comprising
10 in response to determining that one concurrent operation moves one or more locations of a non-fragment unit of the file system to one or more new locations, updating the progress information relating to the one or more locations with the one or more new locations.

10. The method of claim 1, further comprising
15 in response to determining that a write operation replaces one or more sequence tables of the file system by one or more new sequence tables, updating the progress information on the one or more sequence tables with progress information on the one or more new sequence tables.

11. The method of claim 1, further comprising
20 detecting whether there are one or more high priority operations in the one or more concurrent operations, during executing each concurrent operation on a fragment of the file system as identified by the progress info.

12. The method of claim 11, further comprising

D

in response to detecting one or more high priority operations, performing the one or more high priority operations after completing the concurrent operations on the fragment.

13. A system comprising

5 a non-volatile memory,

a volatile memory, and

a processor to store in the volatile memory a data structure that comprises location data associated with one or more concurrent operations to access a file system of the non-volatile memory, and to perform the one or more concurrent
10 operations according to the location data.

14. The system of claim 13, wherein the processor further to initialize the location data to include location data of one or more sectors in the file system, wherein the one or more sectors are operated by the concurrent operations.

15. The system of claim 13, wherein the processor further to obtain
15 addresses of one or more sectors being operated by each concurrent operation from the location data.

16. The system of claim 13, wherein the processor further to perform each concurrent operation on a fragment of the file system as indicated by the location data.

20 17. The system of claim 13, wherein the processor further to delete the location data associated with a concurrent operation on a fragment of the file system, in response to determining that the concurrent operation on the fragment is completed.

18. The system of claim 17, wherein the processor further to continue the
25 concurrent operation on one or more fragments of the file system, in response to

determining that the data structure comprises location data associated with the concurrent operation on the one or more fragments after the deleting.

19. The system of claim 13, wherein the processor further to removing the location data on a concurrent operation from the data structure, in response to
5 determining that the concurrent operation is completed.

20. The system of claim 13, wherein in response that a concurrent operation on a fragment of the file system replaces existing location data on one or more sectors of the file system, the processor further to update location data associated with one or more other concurrent operations on the same one or more sectors
10 according to the replacement.

21. The system of claim 20, wherein in response to determining that the concurrent operation replaces the existing location data by new location data, the processor further to update the location data associated with the one or more other concurrent operations with the new location data.

15 22. The system of claim 13, wherein in response that a write operation on a fragment of the file system replaces one or more exiting sector locations of the file system by one or more new sector locations, the processor further to update the same one or more existing sector locations in location data on one or more other concurrent operations with the one or more new sector locations.

20 23. The system of claim 13, wherein in response to determining that one or more high priority operations are detected during a concurrent operation, the processor further to perform the one or more high priority operations after completing the concurrent operation on a fragment of the file system as identified by the location data.



24. A machine readable medium comprising a plurality of instructions that in response to being executed result in a computing device

storing a track table, wherein each entry of the track table comprises one or more sector locations of a file system of a non-volatile memory being operated by

5 one or more concurrent operations, and

performing the one or more concurrent operations on the one or more sector locations.

25. The machine readable medium of claim 24 further comprising a plurality of instructions that in response to being executed result in a computing device

10 initializing the track table to further include information to identify at least one of files and directories in the file system being operated by one or more of the concurrent operations.

26. The machine readable medium of claim 24 further comprising a plurality of instructions that in response to being executed result in a computing device

15 performing each concurrent operation on a corresponding fragment of the file system as indicated by one or more sector locations associated with the concurrent operation.

27. The machine readable medium of claim 24 further comprising a plurality of instructions that in response to being executed result in a computing device

20 deleting from the track table one or more sector locations associated with a concurrent operation on a fragment of the file system, in response to determining that the concurrent operation on the fragment is completed.

28. The machine readable medium of claim 27 further comprising a plurality of instructions that in response to being executed result in a computing device



in response to determining that the track table comprises one or more sector locations associated with the concurrent operation after the deleting, continuing the concurrent operation on a fragment identified by the one or more sector locations.

29. The machine readable medium of claim 24 further comprising a plurality
5 of instructions that in response to being executed result in a computing device removing from the track table an entry associated with a concurrent operation in response to determining that the concurrent operation is completed.

30. The machine readable medium of claim 24 further comprising a plurality
of instructions that in response to being executed result in a computing device
10 in response to determining that a concurrent operation moves a sector location to a new sector location, updating one or more entries of the track table that relate to the sector location with the new sector location.

31. The machine readable medium of claim 24 further comprising a plurality
of instructions that in response to being executed result in a computing device
15 in response to determining that a concurrent operation on a fragment replaces a sequence table by a new sequence table, updating one or more entries of the track table that comprise sector locations of the one or more sequence tables with sector locations of the one or more new sequence tables.



ABSTRACT

A method may be used in a multi-threading non-volatile memory file system.

The method comprises creating a data structure to store progress information on one or more concurrent operations to access a file system of a non-volatile memory;

5 and executing the one or more concurrent operations based on the progress info.





FIG. 1

100

130






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7